

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Brother | Logo |
|------------------------|------------------------------|------|
| Company name * | Brother International Europe | |
| Contact information * | Stephen Kimber | |
| e-mail address | steve.kimber@brother.co.uk | |
| Internet site * | www.brother.com | |
| Additional information | | |

 The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.

 Type of product *
 All-In-One Electro-photographic Printer

 Commercial name *
 DCP-L2532DW

 Model number *
 DCP-L2532DW

 Issue date *
 22/February/2018

 Intended market *
 Global Europe Asia, Pacific & Japan Americas Other

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model number * | | DCP-L2532DW | Logo | | | | | |
|----------------|--|--|------------------|-------------|--|-------------|--|--|
| Issue date * | | 22/February/2018 | | | | | | |
| Product | uct environmental attributes - Legal requirements | | | | | met | | |
| Item | •••••• | | | | | | | |
| P1 | Hazardo | ous substances and preparations | | | | | | |
| P1.1* | | s do comply with the current European RoHS Directive. (See legal reference and N | IOTE B1) | \square | | | | |
| P1.2* | Products do not contain Asbestos (see legal reference). | | | | | | | |
| P1.3* | | nt: Legal reference has no maximum concentration value. | | \boxtimes | | | | |
| 1 1.0 | .3* Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values. | | | | | | | |
| P1.4* | Products | s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych /l (PCT) in preparations (see legal reference). | nlorinated | \boxtimes | | | | |
| P1.5* | Products | s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 car intaining at least 48% per mass of chlorine in the SCCP (see legal reference). | bon atoms in the | € 🛛 | | | | |
| P1.6* | (see leg | th direct and prolonged skin contact do not release nickel in concentrations above (al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5. | 0,5 μg/cm²/week | | | \square | | |
| P1.7* | REACH | Article 33 information about substances in articles is available at (add URL or mail other.eu/reach | contact): | \square | | | | |
| P2 | Batterie | S | | | | | | |
| P2.1* | | oduct contains a battery or an accumulator, the battery/accumulator is labeled with Information on proper disposal is provided in user manual. (See legal reference) | the disposal | | | \boxtimes | | |
| P2.2* | | s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadr | nium. (See legal | | | \square | | |
| P2.3* | Batteries | s and accumulators are readily removable. (See legal reference) | | | | \boxtimes | | |
| P3 | Conforr | nity verification & Eco design (ErP) | | | | | | |
| P3.1* | The Dec http://si | duct is CE-marked to show conformance with applicable legal requirements (see le claration of Conformity can be requested at (add link or e-mail address): upport.brother.com/g/b/manuallist.aspx?c=gb⟨=en∏=dcpl2530dw_e 3=371&type2=101 | | | | | | |
| P3.2* | The proc | duct complies with the Eco design requirements for energy-related products, | | \square | | | | |
| | (see legal reference). Required information is; given in item P15 or added to this document, | | | | | | | |
| | h the allo | available at (add URL): | | | | | | |
| | | upport.brother.com/g/b/manuallist.aspx?c=gb⟨=en∏=dcpl2530dw_e 3=371&type2=101 | u∠⃒=Englis | | | | | |
| P4 | | nable materials | | | | | | |
| P4.1* | If a phot | o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and NOTE B1). | ax 0,01% (see | | | | | |
| P4.2* | - | her is used in the product, it does not contain cadmium max 0,1% by weight (see le | gal reference). | \square | | | | |
| P4.3* | are Corr applicab | /toner formulation/preparation is classified as hazardous or contains a substance formunity workplace exposure limits, the product/packaging is adequately labeled active regulations and a Safety Data Sheet (SDS) in accordance with these requirement | cording to | | | | | |
| DE | | al reference). | | | | | | |
| P5.1* | | t packaging | av oodmium oo | | | | | |
| | hexavale | ng and packaging components do not contain more than 0,01% lead, mercur ent chromium by weight of these together. | - | | | | | |
| P5.2* | used (se | kaging materials are marked with abbreviations and numbers indicating the nature e legal reference). | , | | | | | |
| P5.3* | Protocol | duct packaging material is free from ozone depleting substances as specified (see legal reference). | in the Montrea | al 🔀 | | | | |
| DC | | nt: Legal reference has no maximum concentration values. | | | | | | |
| P6 | | nt information | | | | | | |
| P6.1* | mormat | ion for recyclers/treatment facilities is available (see legal reference). | | \bowtie | | | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model nu | umber * | DCP-L2532DW | Logo | | | | | |
|--------------|---|---|----------------|-------------|-------------|----------|--|--|
| Issue date * | | 22/February/2018 | | | | | | |
| | | | | | | | | |
| | | mental attributes - Market requirements (See General NOTE GN below) mental conscious design | | Require | ement | met | | |
| Item | | tory to fill in. Additional information regarding each item may be found under P14. | | Yes | No | | | |
| P7 | Design | | | | | | | |
| D7.4* | | nbly, recycling | | | | | | |
| P7.1* | | t have to be treated separately are easily separable | | | <u> </u> | _Ц_ | | |
| P7.2* | | aterials in covers/housing have no surface coating. | | | <u> </u> | <u> </u> | | |
| P7.3* | | arts > 100 g consist of one material or of easily separable materials. | | | | | | |
| P7.4* | | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | | | | | |
| P7.5 | - | arts are free from metal inlays or have inlays that can be removed with commonly av | ailable tools. | \square | | | | |
| P7.6* | Labels ar | e easily separable. (This requirement does not apply to safety/regulatory labels). | | \boxtimes | | | | |
| | Product | | | | | | | |
| P7.7* | | g can be done e.g. with processor, memory, cards or drives | | | | | | |
| P7.8* | | g can be done using commonly available tools | | | \boxtimes | | | |
| P7.9. | Spare pa | rts are available after end of production for: 7 years | | | | | | |
| P7.10 | Service is | s available after end of production for: 7years | | | | | | |
| | Material | and substance requirements | | | | | | |
| P7.11* | | cover/housing material type (e.g. plastics, metal, aluminum): | | | | | | |
| D7 40 | | | type: ABS | | | | | |
| P7.12 | | n materials of external electrical cables are PVC free. | | <u> </u> | | <u> </u> | | |
| P7.13 | | n materials of internal electrical cables are PVC free. | | | | <u> </u> | | |
| P7.14 | External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. | | | | | | | |
| P7.15 | Printed of | sircuit boards, PCBs (without components) are low halogen: all PCBs > 28 as defined in IEC 61249-2-21. (See NOTE B2) | 5g 🗌 are lo | w 🗌 | \boxtimes | | | |
| P7.16 | Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: \square | | | | | | | |
| P7.17 | | emical specifications of flame retardants in printed circuit boards > 25 g (without cor | nponents): | | | | | |
| | TBBPA (| additive) 🔀, TBBPA (reactive) 🔀 (See NOTE B3), Other; chemical name: | , CAS #: | \boxtimes | | | | |
| | | emical specifications of flame retardants in printed circuit boards (without componer pISO 1043-4: | nts) > 25 g | | | | | |
| P7.18 | <u>Alt. 1:</u> Fla | ame retarded plastic parts > 25 g contain the following flame retardant substances, ations above 0,1%: | /preparations | in | | | | |
| | 2. Chemi | cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " cal name: , CAS #: " | | | | | | |
| | <u>Alt. 2: </u> Ch FR(17), I | nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043 $\frac{1}{R(40)}$ | -4: | \boxtimes | | | | |
| P7.19 | assigned | parts > 25 g, flame retardant substances/preparations above 0,1% are used which I the following Risk phrases; and Hazard statements: | | | | | | |
| | | | IOTE B5) | | | | | |
| P7.20* | | umer recycled plastic material content is used in the product (See NOTE B6): | | \boxtimes | | | | |
| | a) Of to perc | t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content entage of total plastic by weight) is 0.1 %. | (calculated as | а | | | | |
| | or b) The | weight of recycled material is g. | | | | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model nun | nber * | DCP-L253 | 2DW | | | Logo | | | |
|---|---|---------------|---|----------------------------------|--|-----------------|--------------|---------|-------------------|
| Issue date | * | 22/Februa | ry/2018 | | | | | | |
| Product of | environr | nental attr | ibutes - Market ree | quirements (conti | nued) | | Requ | uiremen | t met |
| Item | | | | | - | | Ý | es No | n.a. |
| D7 04* | | | ance requirements (c | | | | | | |
| P7.21* | | • | terial content is used i | | , | | L | | |
| | If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as total plastic by weight) is %. or | | | | | | entage of | | |
| | b) The weight of the biobased plastic material is g. | | | | | | | | |
| P7.22* | | | e from mercury, i.e. le becify: Number of lamp | | um mercury content pe | r lamp: ı | mg | | |
| P8 | Batterie | - | | | | | | | |
| P8.1* | • | hemical cor | • | | | | | | |
| P9 P9.1 | | - | on (See NOTE B8) | | ons are reported: | | | | |
| | - | | Power level at | Power level at | Power level at | Reference/St | ondord for | 00000 | |
| Energy mo | | | 100 V AC | 115 V AC | 230 V AC | modes and te | | energy | |
| Sleep mod STAR® Op (OM) produ | perational | | W | W | W | | | | |
| Standby/of ENERGY \$ | f mode fo STAR Ope | erational | W | W | W | | | | |
| Mode (OM) products TEC value for ENERGY STAR TEC products | | | kWh/week | kWh/week | 1.232 kWh/week | | | | |
| (TEC= Typ | ical Energ | av | | | | | | | |
| Printing | | ,, | W | W | Approx. 440 W | | | | |
| Copying | | | W | W | Approx. 455 W | | | | |
| Quiet Mo | de/Copyi | ing | W | W | Approx. 260 W | | | | Ē |
| Quiet Mo | de/Printi | ng | W | W | Approx. 260 W | | | | |
| Ready | | | W | W | Approx. 42 W | | | | $\overline{}$ |
| Sleep | | | W | W | Approx. 6.2 W | | | | Π |
| Deep Sle | ep | | W | W | Approx. 0.9W | | | | $\overline{\neg}$ |
| Power O | ff | | W | W | Approx. 0.03 W | | | | Ē |
| Networke | ed Standl | by | W | W | Approx. 4.9 W | | | | |
| External Po | ower Supr | oly Efficienc | y Level (International I | Efficiency Marking Pr | otocol) * : | | | | |
| Print/Scan | | | 30 images per seco | | , | | | | |
| Default tim | e to enter | energy sav | e mode: 1 minu | tes | | | | | |
| P9.2* | Informat | ion about th | e energy save function | n is provided with the | product. | | | | |
| P10 | Emissio | | | | | | | | |
| D10.4 | | | eclared according to | | | olabted as used | nower lovel | | |
| P10.1 | Mode | | ode description | | atistical upper limit A-w _{WA,c} (B) | eignted sound | power level, | | |
| | Idle | * | | * | | | | | |
| | Operatio | | Printing(mono) | * | 6.48 | | | | |
| | Other me | | | | | | | | |
| | Measure | ed according | | ECMA-74 UZ205 (only if not co | $\Delta v = CM \Delta - 74$ | | | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| Issue date | e * | 22/Echruoru/201 | | | | | | | | | | |
|------------|--|--|----------------|--------------------------------|-------------------------------|---------------|------------|-------------|--------------------------------------|-------------|------|-----|
| | | 22/February/2018 | | | | | | | | | | |
| Product | environ | mental attribute | s - Market | requirements | (continued) | | | | Req | uiren | nent | me |
| ltem | | | | - | • | | | | Ì | Yes | No | n.a |
| | Chemic | cal emissions from | n printing p | oducts (See NO | DTE B10) | | | | | | | |
| P10.2* | | rformed according ent (ISO/IEC 2836 | _ | | | sion Rates | s from Ele | ectronic | ļ | \boxtimes | | |
| P10.3 | Typical | emission rate (ope | ration phase |) is (mg/h): | | | | | | | | |
| | Electro | photographic devic | es: Ozone | Dust | Styrene | Benze | ene | TVOC | | | | Г |
| | Ink dev | ices: | | Dust | Styrene | Benze | ene | TVOC | | | | Ē |
| | Note: c | ompliance with max | kimum emiss | ion rates in eco l | abels to be declar | ed in P14 | | | | | | |
| P11 | Consu | mable materials for | or printing p | roducts | | | | | | | | |
| P11.1* | A Safet | y Data Sheet (SDS |) is available | for the ink/toner | preparation, even | n if not lega | ally requi | red (see P | 4.3). | \boxtimes | | |
| P11.2* | EN 122 | | | | | d that it r | neets the | e requirem | ents of | \boxtimes | | |
| P11.3* | 2-sided | (duplex) printing/c | opying is an i | ntegrated produc | ct function. | | | | | \boxtimes | | |
| P11.4* | The product is delivered to end-user with default auto-duplex enabled. | | | | | | | | | | | |
| P13 | Packag | ing and documen | tation | | | | | | | | | |
| P13.1* | Product packaging material type(s): CRGTD-FBRBRD weight (kg): 2.20 Product packaging material type(s): PS-E weight (kg): 0.45 Product packaging material type(s): HDPE weight (kg): 0.08 | | | | | | | | | | | |
| P13.2* | Product | t plastic primary pa | ckaging is fre | e from PVC. | | | | | | \boxtimes | | |
| P13.3* | • | duct primary corruner recovered fiber | - | oard packaging, 50 % | specify the conta | ained per | centage | of minimu | n post- | | | |
| P13.4* | | media for user and nic \square , Paper \square , | | umentation (tick | box): | | | | | | | |
| P13.5 | (Please User ar If Yes, j | e only complete this ad product docume please specify: | item if pape | | | | | | | | | |
| | | chlorine-free | | | | | | | | | | |
| | | tal chlorine-free | | | | | | | | | | |
| | Process | sed chlorine-free | | | | | | | | | | |
| P14 | | ary programs: | | | | | | | | | | |
| P14.1 | The pro | duct meets the req | uirements of | the following vol | untary program(s) |): | | | | | | |
| | | BY STAR® el: Blue Angel | | ersion: 2.0 ersion: RAL-UZ2 | Date: 7/Jul 205 Date:27/Ju | • | | t category: | Imaging E Office Equal Printing F | uipme | ent | |
| | Eco-lab | el: | Criteria v | ersion: | Date: | | Product | category: | | anod | | |
| P15 | Additio | nal information (S | See NOTE B | 11) | | | | | | | | |
| | | | | | | | | | | | | |

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

| Reference | Declaration item |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1, P4.1 |
| (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances) | P1.3, 5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| "REACH" Regulation (1907/2006), annex VII | P1.10 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II) | P4.3 |
| Regulation (EC) 1272/2008 (CLP Regulation) | P4.3, P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |