# Quick Setup Guide

Read the *Product Safety Guide* first, then read this *Quick Setup Guide* for the correct installation procedure.

The latest manuals are available at the Brother Solutions Center: support.brother.com/manuals D00WMJ001-02 CEE-ENG Version B



## Unpack the machine and check the components

The components included in the box may differ depending on your country. Remove the protective tape and film covering the machine and the ink tank cover.








Watch our FAQ videos for help with setting up your Brother machine. support.brother.com/videos



#### Inbox Ink Bottles\*

- Black
- YellowCvan
- CyanMagenta
- \* Inbox ink bottles contain the following yield of replacement bottles:
- Black: approx. 95% yieldOthers: approx. 90% yield
- >> Reference Guide: Supply Specifications



Quick Setup Guide Product Safety Guide



**Brother Installation Disc** 

#### **NOTE**

- The *Reference Guide* for these models is available on the enclosed installation disc.
- The illustrations in this *Quick Setup Guide* show the DCP-T710W.
- Save all packing materials and the box in case you must ship your machine.
- You must purchase the correct interface cable for the interface you want to use. A USB cable is included with some models.

#### USB cable

We recommend using a USB 2.0 cable (Type A/B) that is no more than 2 metres long.

#### Secure Network Access

Your machine's default password is on the label on the back of the machine (preceded by "Pwd"). We strongly recommend you change it to protect your machine from unauthorised access.




# Load paper in the paper tray


For more information about paper handling and sizes, see the Reference Guide.



Pull the paper tray completely out of the machine.



Open the output paper tray cover 1.



Adjust the paper guides.

Fan the paper well and load it in the tray.



Close the output paper tray cover, and then slowly push the tray completely into the machine.

#### NOTE

Pull out the paper support ①, and unfold the paper support flap ② so that the printed pages do not fall.





# Connect the power cord

Connect the power cord. The machine will power on automatically.



# Select your country or language (Initial setup only)

After turning the machine on, you may need to set your country or language (depending on your machine). If required, follow the steps on the LCD.



# Set the date and time

Press ▲ or ▼ to select the number, and then press **OK** to set the date and time.





**Power Cord** 

### Fill the ink tanks with the inbox ink


#### IMPORTANT

Check the ink bottle model name on the label. Incorrect ink may cause damage to the machine.






Open the ink tank cover **1** and pull the tab **2** downwards to open the cap of the ink tank.




Remove the cap and protective film from the ink bottle, and then replace the cap.

#### NOTE Fasten f


Fasten the ink bottle cap tightly to avoid leakage.



Remove the tip of the ink bottle. Insert the nozzle of the ink bottle firmly so that the ink does not spill. Fill the ink tank by gently squeezing the bottle as shown. Empty the entire bottle into the ink tank.



Point the nozzle upward so that the ink does not spill, and then remove the nozzle from the ink tank.



Push down on the cap of the ink tank to close it tightly. Repeat step 6 for the three other ink tanks.

Close the ink tank cover. The machine will prepare the ink tube system for printing.




# **Machine settings**

When the machine has finished the initial cleaning process, follow the steps on the LCD to configure the machine settings.

- Check print quality
- Print the installation sheet

#### NOTE

Refer to the sample below to check the print quality.



8

### Select your language (if needed and only for certain models)

- 1. Press Menu.
- 2. Press ▲ or ▼ to select [Initial Setup], and then press OK.
- 3. Press A or V to select [Local Language], and then press OK.
- **4.** Press **△** or **▼** to select your language, and then press **OK**.
- 5. Press Stop/Exit.






### Select a device to connect to your machine





# **Connect your computer**



Put the installation disc into your CD/DVD drive, or download the Full Driver & Software Package at:

For Windows®: support.brother.com/windows For Mac: support.brother.com/mac

If you are using a recently released operating system on your computer, visit the above websites for updated driver and software information.


For Windows®: If the Brother screen does not appear automatically, go to Computer (My Computer/This PC). Double-click the CD/DVD-ROM icon, and then double-click start.exe.

For Mac:

For full driver functionality, we recommend choosing the CUPS driver when adding a printer.

Follow the on-screen instructions and prompts.

For USB Connection: Locate the correct port inside the machine as shown.



**Finished** 

**Can't Connect? Check the following:** 



• USB connection

Restart your wireless access point/router (if possible).

Disconnect the cable.

Restart your machine and computer, and then go to 10

If still not successful, go to 11

Even if you do not have a wireless access point/router, you can connect

your device and your machine directly. For additional wireless network

support, go to support.brother.com/wireless-support.

Brother regularly updates firmware to add features and apply bug fixes.

To check for the latest firmware, visit <u>support.brother.com/up4</u>.

If still not successful, visit support.brother.com for FAQs and Troubleshooting.

**SSID (Network Name)** 

Network key: XXXX

# **Alternative wireless setup** (DCP-T510W/DCP-T710W only)

Find your SSID (Network Name) and Network Key (Password) on your wireless access point/router and write them in the table provided below.

**Network Key (Password)** SSID: XXXXXXX

If you cannot find this information, ask your network administrator or wireless access point/router manufacturer.

- 1. Press Menu.
- 2. Press ▲ or ▼ to select [Network], and then press **OK**.
- Press ▲ or ▼ to select [WLAN], and then press
  - Press ▲ or ▼ to select [Setup Wizard], and then press OK.

Select the SSID (Network Name) for your access point/router and enter the Network Key (Password).

For more information, see *Enter Text* on Your Brother Machine in the Online User's Guide.

When the wireless setup is successful, the LCD displays [Connected].

If setup is not successful, restart your Brother machine and your wireless access point/router, and repeat 11

**For Computer** 

Go to 10 to install software.

**For Mobile Device** 

12 to install apps.

# Print or scan using your mobile device (DCP-T510W/DCP-T710W only)

Your mobile device must be connected to the same wireless network as your Brother machine.

AirPrint is available for all supported iOS devices including iPhone, iPad, and iPod touch. You do not need to download any software to use AirPrint. For more information, see the Online User's Guide.





Apple AirPrint

Works with

Download and install the Mopria® Print Service app from Google Play™ using your Android™ device.



Download and install our free application Brother iPrint&Scan from a mobile application store, such as the App Store, Google Play™, or Microsoft® Store using your mobile device.

Brother SupportCenter is a mobile app that provides the latest support information for your Brother product. Visit the App Store or Google Play™ to download.



#### **Optional apps**

You can print from and scan to your mobile device using various

For instructions, see the Online User's Guide.

