

Important Security Information

You can connect your printer to your computer or mobile device directly using Wireless Direct. Use your computer or mobile device to select the printer's SSID and enter the password if required. The default password is located on the bottom of the printer or inside the battery compartment and marked "WDP".

You can also connect your printer to your computer or mobile device via a Bluetooth®. If a passcode appears on your printer's LCD or on your computer or mobile device while connecting, check that it is the same on both devices, and then press **OK**. If your printer does not have an LCD and the passcode is displayed on your computer or mobile device, press one of the following buttons on your printer:



Bluetooth button



Bluetooth and Wi-Fi® button



Print button

Factory Default Enabled Network Interfaces and Services*

■ Network Interfaces

- Ethernet: Network communication starts when a cable is connected.

■ Network Services

Service	Protocol	Description
Web server	HTTPS/HTTP	The web server is used for viewing and changing the printer's information and settings through Web Based Management and Brother's management tools. It also supports printing using AirPrint and Web Services.
SNMP	SNMP v1/v2c	SNMP is used for viewing and changing the printer's information through Brother's management tools. In the factory default settings, only viewing is enabled.
LPD	LPD	LPD is primarily used for printing.
Port 9100 (Raw Port)	Port 9100	Port 9100 is primarily used for printing. It also supports viewing and changing the printer's information through Brother's management tools. In the factory default settings, only viewing is enabled.
Name resolution	NetBIOS/mDNS/LLMNR	These protocols are used for name resolution.
WS-Discovery	WS-Discovery	WS-Discovery is used for dynamically discovering printers on a network.

*The above services may be disabled by default on some models.

You can disable these services in the left navigation bar on the Web Based Management page by selecting

Network > Network > Protocol. If your model has the **Network** tab at the top of the screen, click this tab and select the **Protocol** option.

Product and Data Security

Product Installation

Unauthorised users may physically access or remotely manipulate the product through the network. Make sure you install the product in a secure location.

Personal Information

The personal information stored in the product may vary depending on the product - for example, it may include print data. Changing the product's settings may increase the risk of unauthorised access to the personal information. Make sure you review the content and impact of the settings before making any changes.

Using Bluetooth®

This product supports BR/EDR Legacy and LE Legacy protocols for Bluetooth connections. These protocols do not offer strong communication security. When connecting devices that use these protocols to your printer, make sure your network environment is protected against unauthorised access before enabling Bluetooth.

Using TFTP

This product supports access to administrator information via TFTP, but this protocol does not guarantee secure network communications and is disabled by default. Make sure your network environment is protected against unauthorised access before enabling the protocol.

About Menu Security Features

The Menu Security features are disabled by default when you purchase the product. For instructions on how to enable them, see your product's User's Guide.

Event Logs

Your printer can log security events related to the firmware. Use Web Based Management to get this information in a CSV file by selecting **General > Maintenance Information > Export**.

Login Password

Event ID	Description
1001	Changed the login password for Web Based Management
1002	Successful login to Web Based Management
1003	Failed login to Web Based Management
1004	Changed the admin password minimum length
1005	Admin locked
1006	Changed the admin lock setting
1007	Changed the On/Off setting for panel security
1008	Successful login to panel
1009	Failed login to panel
1010	Panel locked

Event ID	Description
1011	Successful command authentication
1012	Failed command authentication
1013	Admin locked due to failed command authentication

Security Settings

Event ID	Description
2001	Changed the IP address
2002	Changed the SNMP settings
2003	Changed the firmware update settings
2004	Changed the contact location
2005	Changed the location
2006	Changed the geolocation (latitude)
2007	Changed the geolocation (longitude)
2008	Changed the setting for Web Based Management (HTTP setting)
2009	Changed the LPD setting
2010	Changed the Raw Port setting (HTTP setting)
2011	Changed the IPP setting
2012	Changed the WSD setting (HTTP setting)

Actions

Event ID	Description
3001	Updated firmware
3002	Registered a template
3003	Deleted a template
3004	Registered a database
3005	Deleted a database
3006	Registered a font
3007	Deleted a font
3008	Backed up data to a USB flash drive
3009	Executed a print job (Not recorded on models that support the print log storage feature.)

Other Information

■ Important

- Available features depend on the printer's model. For more information, see your product's User's Guide.

■ Trademarks

- The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Brother Industries, Ltd. is under license. Other trademarks and trade names are those of their respective owners.
- Wi-Fi is a registered trademark of Wi-Fi Alliance®.

- AirPrint is a trademark of Apple Inc., registered in the U.S. and other countries.

Any trade names and product names of companies appearing on Brother products, related documents and any other materials are all trademarks or registered trademarks of those respective companies.

ENG